

QUOTATION

Name of work: Providing light point plug point and exhaust fan point in newly constructed bathroom and repairing of garden light at director residence.

S.No.	Description	Qty.	Unit	Rate (In words & Figures)	Amount
1	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with modular switch, modular plate, suitable GI box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc as required.				
a	Group 'C'	4.00	Points		
2	Supplying and fixing 3 pin, 5 amp. Ceiling rose on the existing junction box/ wooden block including connection etc. as reqd.	2.00	Nos.		
3	Supplying and fixing brass batten/ angle holder including connection etc. as required.	1.00	Nos.		
4	Supplying and making indoor end termination with brass compression gland and aluminium lugs for following size of PVC insulated and PVC sheathed/XLPE aluminium conductor cable of 1.1kV grade as reqd.				
a	2x6 sqmm(19mm)	2.00	Set		
5	Supplying and fixing 5 amps to 32 amps rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load offollowing poles in the existing MCB DB complete with connections, testing and commissioning etc. as required.				
a)	Single Pole	2.00	Nos.		
6	Supplying & Laying of one no. XLPE cable aluminium conductor steel armoured cable of size 2x6sqmm, grade 1.1kV in following manners.				
a	In Ground I/c excavation, sand cushioning protective covering, refilling of earth as reqd.	63.00	Mtr.		
b	In existing Pipe	5.00	Mtr.		
c	In existing open duct	5.00	Mtr.		

S.No.	Description	Qty.	Unit	Rate (In words & Figures)	Amount
7	S & F metal enclosure suitable for DP/TPN MCB / DP ELCB on surface or recessed etc as reqd.	1.00	Nos.		
8	S & F 40 amp to 63 amp rating 240 volts 'C' curve 10 kA MCB of following pole in the existing MCB DB complete with connection, testing & commissioning etc as reqd.				
a)	Double Pole	1.00	Nos.		
9	Supplying of the 20W LED TUBE LIGHT (DOUBLE SIDE CONNECTION) light fixtures complete with full frame, all accessories with lamp as required complete.	1.00	Nos.		
10	Supplying,fixing,testing commissioning of garden light 35W LED postop lantern Luminures. New generation, post-top, energy saving, environmental friendly, long life aesthetically designed with symmetrical light distribution, spun aluminium landscape luminaire with high power LEDs as light source Cat no.RUBYPT35WLED757PSYMTOPC, make:havells or its equivalent, on the existing pole complete as required.	3.00	Nos.		
11	Supplying of the 10W LED Bulkhead LIGHT ec.Cat no.RUGBYNEONFT10WLED860SSYMTOPC as required complete.	1.00	Nos.		
12	Supply, Installation of exhaust fan, 900 rpm 220 volt AC, 50 Hz of following sweep in the existing opening I/c connection, testing, commissioning etc as reqd.				
a)	300 mm	1.00	Nos.		
13	Dismantling cross arm / street light brakcet/street light fitting from pole complete as required.	3.00	Nos.		
Total Rs.					


राघवेन्द्र सिंह
RAGHVENDRA SINGH
 अधिशासी अभियंता (वि०) E.E. (Elect.)
 स०वि०वि० सं० प्र० संस्थान, कांपुर
 I.W.D., I.I.T., Kanpur
