


QUOTATION

Repairing and replacement of street light in the residential area and antragni ground as per enclosed complaints and repairing & Maintenance of residence at south side main drive main drive.

S.No.	Description	Qty.	Unit	Rate	Amount
1	Supplying and fixing 5 amps to 32 amps rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load offollowing poles in the existing MCB DB complete with connections, testing and commissioning etc. as required.				
a)	Single Pole	4.00	Nos.		
2	Fixing of Switch /DB/KWH meter/pole loose wire fuse box of any size on pole/wall with ragbolts, nuts and washers etc. as reqd.	8.00	Nos.		
3	Dismantalling damaged Switch /DB/KWH meter/pole fuse / loose wire box of any size from site and depositing in store I/c cartage etc. as reqd.	8.00	Nos.		
4	Dismentling, and refixing brass compression type gland up to 35 sq. mm. cable	8.00	Nos.		
5	Locating fault in the cable lines with meggar etc and rectifying removing & restoring the same and making good the damages etc as required.	5.00	Nos.		
6	Supplying and drawing of following sizes of FR PVC insulated copper conductor, 3 core round cable of following size in the existing surface/ recessed steel/ PVC conduit as required.				
a	1.5 Sq.mm	20.00	Mtrs.		
7	Supplying & Laying of one no. XLPE cable aluminium conductor steel armoured cable of size 2x10sqmm, grade 1.1kV in following manners.				
a	In Ground I/c excavation, sand cushioning protective covering, refilling of earth as reqd.	60.00	Mtr.		
b	In existing open duct	5.00	Mtr.		

	Description	Qty.	Unit	Rate	Amount
8	S/F testing commissioning of street light Luminures. ENDURA PEARL type 25W LED ENDURAPEARLSL 25WLED757SASYTOPC , die-cast aluminium IP65 electronic Driver,make:havells or its equivalent, on the existing street light pole complete as required.	3.00	Nos.		
9	Making masonry Pillar of size 450mmx450mmx 600mm height above the ground level with bricks, cement and sand duly plastered on all sides,makingood.etc. as required complete.	5.00	Nos.		
10	Supply, Installation, testing & commissioning of AC ceiling fan of following sweep 220 volts without regulator I/c wiring the down rods of standard length up to 30 cm with 1.5 sq.mm. PVC insulated copper conductor single core cable etc as reqd.				
a)	1200 mm	4.00	Nos.		
11	S & F 40 amp to 63 amp rating 240 volts 'C' curve 10 kA MCB of following pole in the existing MCB DB complete with connection, testing & commissioning etc as reqd. (legrand)				
a)	Triple pole & Neutral	1.00	Nos.		
12	Dismantling of any size fan from normal height				
a)	ceiling fan	3.00	Nos.		
13	S&F Connecting and commissioning of single mounted timer switch for 24 Hr. setting complete etc. as required. .For 365 days 24 hrs setting (Astrorex D21) Lerand(.Cat no:412654)	2.00	Nos.		

Total Rs.


राघवेन्द्र सिंह
RAGHVENDRA SINGH
 अधिरात्री अभियंता (वि०) E.E. (Elect.)
 सं०नि०वि०,भा०प्री० संस्थान, कानपुर
 I.W.D., I.I.T., Kanpur

Raghvendra Singh