

QUOTATION


Name of work: Renovation / Modification of electrical installation vacate house no. 227.

S.No.	Description	Qty.	Unit	Rate (in words & figures)	Amount
1	Rewiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable and 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable as earth wire in existing surface/ recessed steel conduit including dismantling as required.				
a	Group 'A'	7.00	points		
2	Supplying & drawing following sizes of FRLS PVC insulated copper conductor, single core cable in the existing surface / recessed steel / PVC conduit as reqd.				
a	1 x 1.5 Sq.mm..	30.00	Mtr.		
b	3 x 1.5 Sq.mm..	20.00	Mtr.		
c	3 x 4 Sq.mm..	15.00	Mtr.		
d	3 x 6 Sq.mm..	10.00	Mtr.		
3	Supplying and drawing following pair 0.5 mm dia FRLS PVC insulated annealed copper conductor, unarmored telephone cable in the existing surface/ recessed steel/ PVC conduit as required.				
a	2 Pair	10.00	Mtr.		
4	S & F following piano type switch /socket on existing switch box/cover I/c connection etc as reqd.				
a	5/6 Amp switch	15.00	Nos.		
b	15/16 Amp. switch	3.00	Nos.		
c	3 Pin 5/6 Amp. socket outlet	5.00	Nos.		
d	6 Pin 15/16 Amp. socket outlet.	3.00	Nos.		
e	Telephone socket outlet	1.00	Nos.		
f	Bell push	1.00	Nos.		

S.No.	Description	Qty.	Unit	Rate (in words & figures)	Amount
5	Supplying and fixing 3 pin, 5 amp. Ceiling rose on the existing junction box/ wooden block including connection etc. as reqd.	5.00	Nos.		
6	Supplying and fixing brass batten/ angle holder including connection etc. as required.	5.00	Nos.		
7	Supplying and fixing following way, single pole and neutral, sheet steel, MCB distribution board, 240 volts, on surface/ recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator).				
a	12-way, Double door	1.00	Nos.		
8	Supplying and fixing 5 amps to 32 amps rating, 240 volts, 'C' series, MCB suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as reqd.				
a	Single Pole	12.00	Nos.		
9	S & F following rating double pole (single phase & neutral) 240 volts RCCB (ELCB), having sensivity current up to 30 mA in the existing MCB DB complete with connection,testing & commissioning etc as reqd.				
a	40 Amp	1.00	Nos.		
10	Fixing of RJ-45 modular box with cover plate or I/o box for internet on surface/ recessed cutting the wall making good the same as required. (box and cover plate will be supplied by dept.)	1.00	Nos.		
11	Drawing of optical cable enhanced cat5/cat6/telephone/networking/power cable in existing steel conduit pipe/GI/HDPE pipe including numbering of networking wire from room to rack as reqd.	10.00	Mtr.		
12	S & F wood board of following sizes on surface or in recessed with suitable size of phenolic laminated sheet cover in the front etc as reqd.				
a	100 mm x 100 mm	15.00	Nos.		
b	175 mm x 100 mm	5.00	Nos.		
c	200 mm x 150 mm	2.00	Nos.		
d	200 mm x 250 mm	1.00	Nos.		
13	Providing and fixing following sizes of PVC casing and capping on surface as reqd.				

S.No.	Description	Qty.	Unit	Rate (in words & figures)	Amount
a	20 x 12 mm	25.00	Mtr.		
b	25 x 16 mm	20.00	Mtr.		
c	32x 16 mm	15.00	Mtr.		
d	38x 16 mm	2.00	Mtr.		
14	S & F following piano type switch /socket on existing switch box/cover I/c connection etc as reqd.				
a	Fan regulator socket type roatary step	2.00	Nos.		
15	Dismantling and refixing of wood board of any size on surface or in recessed etc as reqd.	5.00	Nos.		
16	Dismantling damaged DB/TPN Switches/ loose wire boxes along with all accessories and depositing the same in the store as reqd.	1.00	Nos.		
17	S & F 3 mm thick phenolic laminated sheet on existing board with brass screw & cup washer etc as reqd.	500.00	Sq.inch		
18	Dismantling and refixing of switch / socket /regulator I/c cleaning, connecting, commissioning etc as reqd.	10.00	Nos.		
19	Supply, Installation, testing & commissioning of AC ceiling fan of following sweep 220 volts without regulator I/c wiring the down rods of standard length up to 30 cm with 1.5 sq.mm. PVC insulated copper conductor single core cable etc as reqd.				
a	1200 mm	1.00	Nos.		
20	Supplying fixing erection of wall bracket/ceiling fittings of all sizes and shapes containing upto two GLS lamps per fitting complete with all accessories includng connecting etc as required (without Lamp)				
a	bulkhead for 1x100W GLS	1.00	Nos.		

Total Rs


 राघवेंद्र सिंह
 RAGHENDRA SINGH
 (विद्युत अभियंता (वि.) E.E. (Elect.)
 (कक्षा-01, भारतीय संस्थान, काणपुर
 I.I.T., Kanpur