

QUOTATION

Sub:- Providing input and output connection for UPS alongwith UPSpower points for each room from 571 to 591 at Faculty building 5th floor department of mathematics.

SL No.	DESCRIPTION	QTY	UNIT	RATE (In words & Figures)	AMOUNT
1	Supplying and drawing following sizes of FRLS PVC insulated copper conductor, single core cable in the existing surface/ recessed steel/ PVC conduit as required.				
1.01	3 x 1.5 sq. mm	215.00	Metre		
1.02	3 x 4 sq. mm	50.00	Metre		
1.03	3 x 6 sq. mm	20.00	Metre		
1.04	3 x 10 sq. mm.	5.00	Meter		
2.00	Supply and fixing of 32 x 20 mm DLP mini- trunking white-system with independent cover etc. as required complete.	100.00	Meter		
3.00	Supply and fixing of following accessories suitable for 32 mm x 20 mm size plastic trunking white system.				
3.01	End cap	1.00	Nos.		
3.02	internal / external angle	5.00	Nos.		
3.03	changeable flat angle	16.00	Nos.		
3.04	flat junction	2.00	Nos.		
4.00	Supply and fixing of 105 x 50 mm DLP trunking white-system but without cover and partition etc. as required complete.	3.00	Meter		
5.00	Supply and fixing of following accessories suitable for 105 mm x 50 mm size plastic trunking white system.				

SL No.	DESCRIPTION	QTY	UNIT	RATE (In words & Figures)	AMOUNT
5.01	85 mm flexible cover	3.00	Meter		
5.02	End cap	4.00	Nos.		
6.00	S & F following size of steel flexible pipe along with the accessories on surface etc as required				
6.01	20 mm	10.00	Meter		
6.02	25 mm	5.00	Meter		
7.00	Supplying, installation of Clip-on frame with finishing plate for 85mm cover for DLP plastic trunking 105mm x 50mm etc. as reqd.				
7.01	6 module	16.00	Nos.		
8	Supplying and fixing following modular switch/ socket on the existing clip-on frame fixed on 85mm cover of 105 x 50 mm DLP plastic trunking including connections etc. as required complete.				
8.01	6 A switch	32.00	No.		
8.02	6 A pin 2/3 pin socket outlet	32.00	No.		
9.00	S & F metal enclosure suitable for DP/TPN MCB / DP ELCB on surface or recessed etc as reqd.	3.00	Nos.		
10	Supplying and fixing following way, single pole and neutral, sheet steel, MCB distribution board, 240 V, on surface/ recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator)				
10.01	6 way, Double door	1.00	No.		

SL No.	DESCRIPTION	QTY	UNIT	RATE (In words & Figures)	AMOUNT
--------	-------------	-----	------	------------------------------	--------

10.02	8 way , Double door	2.00	No.		
-------	---------------------	------	-----	--	--

11 Supplying and fixing following rating, 240/415 V, 10 kA, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required.

11.01	Single pole 5 A to 32 A	22.00	No.		
-------	-------------------------	-------	-----	--	--

11.02	Double pole 5 A to 32 A	4.00	No.		
-------	-------------------------	------	-----	--	--

11.03	Double Pole (40A-63A)	1.00	Nos.		
-------	-----------------------	------	------	--	--

Total Rs.

Prima

अधीक्षक अभियन्ता / S.E.
संनिविदा (I.W.D.)
भा.प्रौ. संस्थान, कानपुर
I.I.T., Kanpur